

P

PRODECK™

MINI SCAFFOLD SYSTEM



The most versatile mini-scaffold ever devised.

Prodeck by Equiptec® adapts easily to almost any terrain, ramp or stair, clears obstacles like shrubs, desks or machinery, squeezes through standard doorways and reaches up two and half stories.

Prodeck does all of this with combinations of 10 simple and compact component types. It's effortless to assemble, easy to store and easy to transport.



FREEPHONE

NZ 0800 840 000

AUS 1800 154 396

INTERNATIONAL +64 6 842 0222

www.equiptecscaffold.com

EQUIPTEC®
ELEVATE • PROTECT • ENHANCE

Versatile, adaptable and effortless...



Prodeck is truly a universal design suited to all uses from residential to harsh construction sites.

Commercial workhorse: You can rely on Prodeck to get you there, keep you secure and comply with the current safety codes. Prodeck is built extra strong to take the knocks and abuse on a construction site.

Home Handyman's friend: From exterior and interior building maintenance to tree pruning and hedge trimming, Prodeck will keep you safe and secure at home.

Work up to 6.6 metres: By combining these components you can build a huge range of different configurations enabling you to work from 2.6m to 6.6m high in almost any situation or terrain.

User friendly: All Prodeck components are simple, strong and compact. It's effortless to assemble, easy to store and easy to transport.



Expandable

On the Prodeck system can reach up to 6.6 metres or two and a half stories.



Compact

Ultra-compact when dismantled, Prodeck is easy to transport and store.



Adaptable

Prodeck adapts easily to situations and terrain like stairs and slopes.



Handy

Prodeck fits easily through interior doorways.



Reach to
6.6
metres



2.6m
reach



3.1m
reach



3.6m
reach



4.1m
reach



4.6m
reach



5.1m
reach



5.6m
reach



6.1m
reach



6.6m
reach

9 height options with combinations of these 10 simple component types


PLATFORM

- 225kg capacity each
- Bearer arms stow neatly beside main beam
- Easy to use automatic graspers give firm attachment
- Carry handle for easy lifting



1.5m FRAMES

- 2/pack
- Strong and rugged frame built from high grade 2.6mm thick wall alloy tubing
- Cast spigots are tapered to prevent jamming



2.0m FRAMES

- 2/pack
- Strong and rugged frame built from high grade thick wall alloy tubing
- Cast spigots are tapered to prevent jamming



HANDRAIL FRAMES

- 2/pack
- Strong and rugged frame built from high grade 2.6mm thick wall alloy tubing



HANDRAIL RAILS

- 2/pack
- High grade 2.6mm thick wall alloy tubing
- Pressure die cast graspers automatically lock in place




LADDER

- Fixed in place by 2 graspers
- Strong lightweight construction
- Adjusts for 1.5m or 2.0m heights




OUTRIGGERS

- 2/pack
- 3 fittings = multi adjustable
- Swivel foot fits firmly to the ground
- High grade 2.6mm thick wall alloy tubing




TOEBOARDS

- One piece
- Hinged corners allow for folding when stored
- Fits snugly around platform to prevent tools etc from falling



HANDRAIL TRUSS

- Increases handrail system rigidity
- High grade 2.6mm thick wall alloy tubing
- Pressure die cast graspers automatically lock in place



CASTORS

- 2/pack
- 150mm
- Double pedal
- 300mm height adjustment
- Captive to frame, won't drop out



Specifications

Deck heights from	0.6m to 4.6m	Castor wheel size	150mm
Length	1.7m	Castor height adjustment	300mm
Width	0.63m	Deck surface	Non slip-coated plywood
Capacity	225kg/platform	Aluminium	T6 grade

Complies with AS/NZS 1576 Safety Standards and adheres to the Best Practice Guidelines for Scaffolding.

HEAD OFFICE

P +64 6 842 0222 F +64 6 842 0223
43 Niven Street (P.O. BOX 5107) Onekawa
Napier, New Zealand